



# RectorSeal<sup>®</sup> NoKink<sup>™</sup>

## Flexible Refrigerant Line Connector

### **DESCRIPTION:**

---

RectorSeal<sup>®</sup> NoKink<sup>™</sup> is a flexible refrigerant line connector that allows easier, kink free connections between the refrigerant line and a wall mounted mini split evaporator.

### **CHARACTERISTICS:**

---

- Eliminates kinking of refrigerant line
- 3" copper stubs for quick connection
- Allows for easy flaring
- 1/4", 3/8", 1/2", 5/8", 3/4" and 7/8" sizes available in 36" lengths
- 1/4", 3/8", 1/2" and 5/8" sizes available in 72" lengths

### **APPLICATIONS:**

---

Used for connecting the in-wall refrigerant line to the refrigerant line in the mini split evaporator unit.  
Can be used when installing air conditioning units when connecting either the evaporator or condenser unit.

### **PACKAGING:**

---

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
66731	1/4" x 36" flex hose	4	2	.27
66733	3/8" x 36" flex hose	4	2	.27
66737	1/2" x 36" flex hose	4	2	.27
66735	5/8" x 36" flex hose	4	2	.27
66732	3/4" x 36" flex hose	4	2	
66734	7/8" x 36" flex hose	4	2	
68231	1/4" x 72" flex hose	4	2	
68233	3/8" x 72" flex hose	4	2	
68237	1/2" x 72" flex hose	4	2	
68234	5/8" x 72" flex hose	4	2	


## **INSTRUCTIONS**

**READ ALL DIRECTIONS AND WARNINGS ON LABEL BEFORE USING**

### **Installation Instructions**

1. Attach the RectorSeal® NoKink™ connector to the refrigerant line in the mini split evaporator unit using either silver solder or flaring.
2. Pull the in-wall copper refrigerant line through wall opening and attach it to the other end of the RectorSeal® NoKink™ connector.
3. Feed the in-wall copper refrigerant line and flexible RectorSeal® NoKink™ connector back up into the wall opening, and mount the evaporator to the mounting bracket.

**NOTE:** Insulate per local code



## **PRECAUTIONS**

- Must be insulated per local code.



## **LIMITED WARRANTY**

RectorSeal makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal shall not be liable for incidental or consequential damages.

### **MANUFACTURED BY**

RectorSeal • 2601 Spenwick Drive • Houston, Texas 77055-1035, USA  
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051  
[www.rectorseal.com](http://www.rectorseal.com)